














**Spare parts and accessories**
**Capacity regulators (hot gas bypass), type PMC**

Accessories for PMC	Description	Qty	Code no.
	<b>External pilot connector</b> Weld, PM 5 to 65, ID 12.7 mm/OD 18 mm Weld, PM 80 to 125, ID 12.7 mm/OD 18 mm 1/4 NPT, PM 5 to 65 1/4 NPT, PM 80 to 125 Nipple assembly Damping orifice, dia. 1.0 mm O-ring Gasket	1 1 1 1 1 1 1	<b>027F1048</b> <b>027F1049</b> <b>027B2065</b> <b>027B2066</b>
	<b>Seal kit for external pilot connector</b> Alu gasket Gasket O-ring	4 4 4	<b>027F1004</b>
	<b>Blanking plug</b> Plug Stop plug O-ring Gasket	1 1 1 1	<b>027F1046</b>
	<b>Pressure gauge connector, solder/weld</b> Nipple assembly Alu gasket	1 1	<b>027F2035</b>
	<b>Seal kit for solder/weld pressure gauge connector</b> Alu gasket Alu gasket	10 10	<b>027B2029</b>
	<b>Pressure gauge connector cutting ring connector (Ermeto)</b> 6 mm 10 mm	1 1	<b>027B2063</b> <b>027B2064</b>
	<b>Pressure gauge connector, 1/4 NPT</b>	1	<b>027B2062</b>
	<b>Pressure gauge connector, flare</b> (Must not be used in ammonia systems!) Nipple Schraeder valve Cap Alu gasket	1 1 1 1	<b>027B2041</b>
	<b>Function indicator for PM/PMC 1 and 3, sizes 5 to 65</b> Function indicator assembly Gasket	1 1	<b>027F0085</b>
	<b>CVH pilot valve body</b> weld ID 12.7 mm/OD 18 mm	1	<b>027F1047</b>
	<b>CVH pilot valve body</b> G 1/4 (ISO 228-1)	1	<b>027F1160</b>
	<b>CVH pilot valve body</b> G 1/4 (USAS B2.1-1960)	1	<b>027F1159</b>
	<b>„Strong“ spring for PM 1 and 3, sizes 5 to 25,</b> approx. 45% more closing force	1	<b>027F0662</b>