

060R9765

060R9765

Media: HFC and HCFC refrigerants, oil, air, water

Medium: Kältemittel HFCKW und HFKW, Öl, Luft, Wasser
 Médias: HFC et HCFC, huile, air, eau
 Aplicaciones: Refrigerantes fluorinados HFC/HCFC, aceite, aire, agua
 Mezzo: HFC e HCFC refrigeranti, olio, aria, acqua

Type	Contact system	Ohmic	Inductive FLA	Starting LRA	Voltage
ACB-1UA	SPST-NO	1 A	1 A	6 A	120/240 AC
					250 AC
ACB-1UB	SPST-NC	1 A	1 A	6 A	120/240 AC
					250 AC
ACB-2UA	SPST-NO	8 A	8 A	48 A	120/240 AC
		6 A	6 A	36 A	250 AC
ACB-2UB	SPST-NC	8 A	8 A	48 A	120/240 AC
		6 A	6 A	36 A	250 AC
ACB-4UA	SPST-NO	0.075 A	0.075 A	0.075 A	120/240 AC and 30 DC
					250 AC and 30 DC
ACB-4UB	SPST-NC	0.075 A	0.075 A	0.075 A	120/240 AC and 30 DC
					250 AC and 30 DC
ACB-2UC	SPDT	8 A	8 A	48 A	120/240 AC
		4 A	4 A	24 A	250 AC

Min/Max Temperature

Min/Max Temperatur
 Min/Max Température
 Min/Max Temperatura
 Min/Max Temperatura

Ambient:
 Umgebung:
 Ambiente:
 Ambiente:
 -30 → +85 °C
 -20 → +185°F

Torque:
 Moment:
 Couple de serrage:
 Par de apriete:
 Coppia de serraggio:
 13 - 15 Nm

Media:
 Medium:
 Médias:
 Aplicaciones:
 Mezzo:
 -55 → +135°C
 -70 → +275°C

Soldering

Löten
 Soudage
 Saldatura
 Soldadura

Max. 45 sec. > 45 sec.

Max. 100°C
212°F

Max. 100°C
212°F

Silfoss 15
(15% Ag)

Contact system

Kontaktsystem
 Système de contacts
 Contactos eléctricos
 Tipo di contatti

